

# OBRA-140

## TEK EMİŞLİ RADYAL FANLAR SINGLE INLET CENTRIFUGAL FANS



- 600 m<sup>3</sup>/h – 1.500 m<sup>3</sup>/h hava debisi aralığında çalışmaktadır.
- Gövde DKP sacdan imal edilip paslanmaya karşı elektrostatik toz boya ile korunmuştur.
- Pervane metal galvaniz sacdan imal edilmiştir ve dinamik balansı alınmıştır.
- Fanlarımızın emiş ağızlarında muhafaza teli kullanılarak dışarıdan gelecek yabancı cisimlerin fana zarar vermesi engellenmiştir.
- Opsiyonel olarak hız kontrol cihazı ile hava debisi ve basınç ayarlanabilir.
- Yalıtım : Class B
- Koruma Sınıfı : IP 44

**Kullanım Alanları :** Tavuk çiftlikleri, kalorifer kazanları ve her türlü geniş alan havalandırmalarında kullanılabilir.

- Has air flow between 600 m<sup>3</sup>/h and 1.500 m<sup>3</sup>/h.
- Casing is made from DKP sheet metal and protected from corrosion by electrostatic powder coating.
- Impellers are forward curved and made from galvanized sheet metal.
- Our fans are protected against external objects by installing metal wire to the inlet flange.
- As an option, a speed control device can be used to adjust the air flow and pressure.
- Insulation : Class B
- Protection : IP 44

**Application Areas :** Can be used for ventilation in poultry farms, heating boilers and every wide range environments.

### TEKNİK DEĞERLER / TECHNICAL PARAMETERS

Tip Type	Voltaj Voltage V	Frekans Frequency Hz	Güç Power W	Akım Current A	Kondansatör Capacitor (µF/Volt)	Devir Speed d/d	Hava Debisi Air Flow m <sup>3</sup> /h	Ses Seviyesi Sound Pressure Level dB(A)	Ağırlık Weight Kg	Ambalaj Packing Adet
OBRA-140-2K-M	220	50	370	2,60	5/400	2800	1350	50	8,00	2
OBRA-140-4K-M	220	50	300	2,00	4/400	1400	600	43	7,90	2
OBRA-140-2K-T	380	50	370	3,00	-	2800	1500	52	7,95	2
OBRA-140-4K-T	380	50	250	1,20	-	1400	650	45	7,85	2

Ses seviyesi 3m mesafeden ölçülmüştür. / Sound level has measured at a distance of 3 meters.

### TEKNİK ÇİZİM VE ÖLÇÜLER / TECHNICAL DRAWINGS AND DIMENSIONS

Tip / Type	A	B	C	D	E	F	G	H	I	K	L	M	N	O	P	R
OBRA-140-2K-M	178	180	233	126	175	117	20	275	120	315	161	140	140	161	113	113
OBRA-140-4K-M	178	180	233	126	175	117	20	275	120	315	161	140	140	161	113	113
OBRA-140-2K-T	178	180	233	126	175	117	20	275	120	315	161	140	140	161	113	113
OBRA-140-4K-T	178	180	233	126	175	117	20	275	120	315	161	140	140	161	113	113

Ölçümler mm cinsindedir. / Dimensions are in (mm)

