

THC

SİĞINAK TAZE HAVA CİHAZLARI FILTRATION UNIT



- 450 m³/h - 4.500 m³/h hava debisi aralığında çalışmaktadır.
- Gövde galvaniz sacdan imal edilmiştir.
- Dıştan rotorlu motor kullanılmıştır.
- Pervane galvaniz sacdan imal edilmiştir ve statik balansı alınmıştır.
- Kanala kolay bağlanabilme özelliğine sahiptir.
- Ürün yerinden sökülmeden kapağı açılarak temizlik ve bakımı kolayca yapılabilir.
- Elyaf G4, Karbon AC-100 ve Radyoaktif Hepa filtre olmak üzere üç sıra filtrelidir.
- İçerisinde bulunan filtreler sayesinde siğınak vb. gibi ortamlarda dışarıdaki zararlı ve zehirli gazların içeri girmesini engeller.
- İsteğe bağlı olarak farklı filtreler ile üretilebilir.
- Yalıtım : Class B
- Koruma Sınıfı : IP 44

- Has airflow between 450 m³/h – 4.500 m³/h.
- Casing is made from galvanised sheet metal.
- Impeller is made from galvanised sheet metal and dynamically balanced.
- Equipped with external rotor motor.
- It has three stages filtration system with fiber G4, carbon AC-100 and radioactive hepa filters
- Can be manufactured with different filtes according to request.
- Through to filtration system it has, it can be used the places like sanctuary. It does block to toxic and harmful air getting inside the room.
- It is easy to clean and maintenance without remove from the place installed by opening the cover.
- Insulation : Class B
- Protection : IP 44

Kullanım Alanları : Tüm siğınak uygulamalarında kullanılabilir.

Application Areas : Can be used for all kind of sanctuary applications.

TEKNİK DEĞERLER / TECHNICAL PARAMETERS

| Tip Type | Frekans Frequency Hz | Hava Debisi Air Flow m ³ /h | Basınç Pressure Pa | 1. Sıra / Stage Elyaf / Fiber | Filtreler / Filters 2. Sıra / Stage Karbon / Carbon | 3. Sıra / Stage Hepa |
|-------------|----------------------------|----------------------------------------------|--------------------------|----------------------------------|-----------------------------------------------------------|-------------------------|
| THC-450 | 50 | 450 | 200 | G4 | AC-100 | Radyoaktif |
| THC-750 | 50 | 750 | 200 | G4 | AC-100 | Radyoaktif |
| THC-1200 | 50 | 1200 | 200 | G4 | AC-100 | Radyoaktif |
| THC-2000 | 50 | 2000 | 200 | G4 | AC-100 | Radyoaktif |
| THC-3000 | 50 | 3000 | 200 | G4 | AC-100 | Radyoaktif |
| THC-4500 | 50 | 4500 | 200 | G4 | AC-100 | Radyoaktif |

TEKNİK ÇİZİM VE ÖLÇÜLER / TECHNICAL DRAWINGS AND DIMENSIONS

| Tip / Type | L | W | H |
|------------|------|------|-----|
| THC-450 | 1000 | 500 | 300 |
| THC-750 | 1200 | 600 | 350 |
| THC-1200 | 1200 | 700 | 350 |
| THC-2000 | 1400 | 800 | 450 |
| THC-3000 | 1400 | 900 | 500 |
| THC-4500 | 1500 | 1000 | 500 |

Ölçümler mm cinsindedir. / Dimensions are in (mm)

