

BREEZE

Tip Type	A	X	E	d	C
BREEZE 4C	175	220	74	98	44
BREEZE 5C	190	237	79	123	52



Düşük Enerji Tüketimi
Low Power Consumption



IP25
IP25



Motor Isınma Koruması
Motor Overheat Protection





ABS
ABS



Rulmanlı Motor
Ball-bearing Motor



Klapeli
Back-flow Valve



TEKNİK DEĞERLER / TECHNICAL PARAMETERS

Tip Type	Çap Diameter	Voltaj Voltage	Güç Power	Hava Debisi Air Flow	Basınç Pressure	Anlık Tüketim C. Consumption	Ses Seviyesi Sound Pressure Level	Ambalaj Packing
	Mm	V	Kw	m ³ /h	Pa	A	dB(A)	Adet
BREEZE 4C	100	220	9	90	36	0,04	25	8
BREEZE 4C MR	100	220	9	90	36	0,04	25	8
BREEZE 4C MRH	100	220	9	90	36	0,04	25	8
BREEZE 5C	125	220	13	165	56	0,06	30	8
BREEZE 5C MR	125	220	13	165	56	0,06	30	8
BREEZE 5C MRH	125	220	13	165	56	0,06	30	8

MR



Zamanlayıcı ve ışık
sensörü içeren çok modlu
fan yöneticisi

MRh



Zamanlayıcı, ışık sensörü
ve nem sensörü içeren
çok modlu fan yöneticisi